

Purolite® IP1

**Polyethylene Inert Polymer,
Downflow Service Packed Beds**

PRINCIPAL APPLICATIONS

- Strainer guard for downflow service packed bed systems

ADVANTAGES

- Protects upper nozzle plates from blockage
- Allows passage of suspended solids in regeneration
- Floats in water

SYSTEMS

- Upflow-regenerated packed bed systems

REGULATORY APPROVALS

- IFANCA Halal Certified
- Kosher Certified

TYPICAL PACKAGING

- 1 CF Box
- 5 CF Drum (Fiber)
- 42 CF Supersack

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Polyethylene
Appearance	Beadlike droplets
Particle Size Range	2.5 - 4 mm
Specific Gravity	0.91 - 0.95
Shipping Weight (approx.)	540 - 560 g/L (33.8 - 35.0 lb/ft ³)
Temperature Limit	100 °C (212.0 °F)



Americas
T +1 610 668 9090
F +1 610 668 8139
americas@purolite.com

Europe
T +44 1443 229334
F +44 1443 227073
europe@purolite.com

Asia Pacific
T +86 571 876 31382
F +86 571 876 31385
asiapacific@purolite.com